

# UD503D

Family	Professional dishwasher
Subfamily	Undercounter dishwashers
Line	Ecoline
Basket dimensions	500x500 mm
Washing pump	Standard



## Accessories Included

Dish basket	1x PB50D01	Water supply hose	Yes - 1,5m
Cutlery basket	1x PHOOS02	Drain hose	Yes - 2m
Flat basket	1x PB50G02		

## Target

Solutions	Hotels; Restaurants/Pubs; QSR
-----------	----------------------------------

## Programs

Programs	3 automatic programs; Self-cleaning programs
Program options	Extra rinse; Clean water cycle
Program specifications	Boiler 85°C/Tank 60°C - 2'30"; Boiler 85°C/Tank 60°C - 4'; Boiler 85°C/Tank 60°C - 1'30"
Maximum basket/hour	40
Maximum dishes/hour	720

## Interface

Display	4 digit	On/Off button	Yes
Number of buttons	5	Manual diagnostic	Yes

## Construction

<b>Tank</b>	With printed base	<b>Rack guides</b>	Embossed
<b>Construction</b>	Partial double wall	<b>Hood elevation system</b>	Manual
<b>Tank material</b>	Stainless steel AISI 304	<b>Filter</b>	4-stages filter system
<b>Back panel</b>	Galvanized	<b>Tank capacity</b>	16 l
<b>Door</b>	Double wall	<b>Boiler capacity</b>	6 l
<b>Upper washing system</b>	One washing and one split rinse spray arms, stainless steel	<b>Noise</b>	Lpa 55,5 dBA
<b>Lower washing system</b>	One washing and one combined rinse spray arms, stainless steel and plastic	<b>Protection class</b>	IPX4
<b>Tank filter</b>	Plastic	<b>Adjustable feet</b>	Yes
<b>Door gasket</b>	Only up	<b>Drain max. height</b>	600 mm

## Technical Features


<b>Tank heating element power</b>	2000 W	<b>Max water hardness</b>	12°f - 7°dH
<b>Boiler heating element power</b>	4960 W	<b>Inlet pressure</b>	2,5-6 bar / 250-600 kPa
<b>Washing pump power</b>	680 W	<b>Detergent load</b>	1,5 l/h
<b>Default connection</b>	5650 W	<b>Rinse load</b>	0,4 l/h
<b>Water cycle consumption</b>	3,2 l	<b>Usable load height</b>	340 mm
<b>Min. water connection temperature</b>	8°C	<b>Depth with open door</b>	1000 mm
<b>Max temperature inlet water</b>	60°C	<b>Product dimensions WxDxH</b>	578x600x814 mm

## Electrical Connection

<b>Power connection</b>	400 V 3N~ / 12 A / 5,7 kW / 50 Hz	<b>Optional electrical connection</b>	230 V 3~ / 16 A / 5,7 kW / 50 Hz; 220 V~ / 12 A / 2,7 kW / 50 Hz; 220 V~ / 14 A / 3,1 kW / 50 Hz; 220 V~ / 18 A / 4.0 kW / 50 Hz
-------------------------	-----------------------------------	---------------------------------------	--

## Equipments

<b>Drain pump</b>	Yes	<b>Automatic start</b>	Yes, default OFF
<b>Peristaltic detergent doser</b>	Electronic control	<b>Cycle counter</b>	Yes
<b>Peristaltic rinse-aid doser</b>	Electronic control	<b>Partial renewal of water in the tank and built-in drain pump</b>	Yes
<b>Default chemicals dosing unit of measure</b>	gr/lt	<b>Water supply pipe diameter</b>	DN15 - ½"
<b>Boiler thermostop</b>	Yes - default	<b>Drain supply pipe diameter</b>	DN20-G 3/4"
<b>Tank thermostop</b>	Yes	<b>Detergent (red) hose lenght</b>	2,2m
<b>Soft Start system</b>	Yes	<b>Rinse aid (blue) hose lenght</b>	2,2m
<b>Stand-by system</b>	Yes		



R	Pannello retro	Lower back panel
Q	Morsetto equipotenziale	Earth terminal
C	Tubo di carico	Filler hose
S	Tubo di scarico	Drain hose
P	Tubi pompe peristaltiche	Peristaltic hoses
E	Cavo alimentazione elettrica	Electricity supply cable

## Not included accessories



### WB50PG5

Wire basket for no. 25 plastic glasses with flat bottom, 500x500x260 mm




### WH00S01

Wire insert for 12 small dishes



### PHOOS01

Polypropylene single basket for cutlery




### PB50G02

Universal flat bottom polypropylene basket, 500x500x170 mm



### WB50T02

Wire basket for 7 trays GN1/1 h 20 mm, 500x500 mm



### WB50G01

Universal wire basket with flat bottom, 500x500x123 mm




### PB50D01

Polypylene basket for 18 plates, 500x500x105 mm



### WB50G02

Wire basket for 90 mm diameter max glasses with sloped bottom, 500x500x170 mm




### WB50G04

Wire basket for glasses 135 mm diameter max, with sloped bottom, 500x500x170 mm



### PHOOS02

6 compartments polypropylene basket for cutlery



### WB50D01

Wire basket for 18 dishes 250 mm max. diameter or self service trays, 500x500 mm



### WB50G03

Wire basket for 72 mm diameter glasses with inclined bottom, 500x500x235 mm



### WS5

Underframe for glasswashers and dishwashers 500, 595x595x490 mm